

Low temperature water-glycol chillers

ISO 9001:2008 & 10014:2007
certified Quality Management System



Main features

- Available in 6 power ratings.
- Air condensed.
- Stainless steel circulation pump.
- Tank equipped with top-up system and sight level.
- High performance alternative compressors with low energy consumption.
- Electronic microprocessor thermoregulator for fluid temperature control and display.
- Cooler malfunction signals on display.
- High efficiency heat exchangers.
- Protective flow switch.
- Low-noise axial fans.
- Bypass on the hydraulic circuit.
- Protective metal frame made of S235 steel painted with epoxy powder and with a semi-gloss textured effect.
- Eco-friendly refrigerant gas (HFC).

Accessories

- High head circulation pumps.
- Water flow switches with fixed settings or settable options and malfunction signal setup.
- Washable water filters.
- Pressure gauges on the hydraulic circuit and/or the cooling circuit.
- Automatic bypass valve of the hydraulic circuit.
- External bypass.
- Caster wheels.
- Metal washable air filters for condenser protection.
- Chiller remote malfunction signal.
- Electric connectors upon client's request.
- PID control for an improved fluid temperature control, with electronic thermoregulator equipped with Autotuning settings.
- Special power supply voltages.
- Configuration for an ambient temperature up to +55°C.
- Configuration for an ambient temperature down to -15°C.
- Frame available upon request in every type of RAL finish or polished stainless steel.
- Hydraulic section made up of check valve on fluid outflow, electric valve on return and water filter to protect the electric valve.
- Minimum electric water level, with remote alarm.

- Automatic water filling system in the hydraulic circuit.
- Non-polluting hydraulic circulation with special fittings, resistant to every type of liquid.
- Hydraulic fittings for food use.

Compact and efficient, LTW coolers are recommended in industrial processes requiring low working temperatures, and are optimised for functioning with a high percentage of glycol water. The working range can be set between -10 and -25°C.

The skills and the experience gained by Euro Cold during its 25 years of experience in the field are at your disposal.

Our power is our ability to respond to the needs of mechanical and industrial systems' manufacturers which are rapidly and constantly changing.

Do not hesitate to contact us in order that we may provide you with the most adequate solution to your specific temperature control needs.

Technical data

MODEL	LTW						
	50	60	95	100	200	250	
Nominal cooling capacity (*)	W	1710	2510	4420	5700	8570	11150
Power supply		400V / 3ph / 50Hz					
Compressor (Max. absorbed power)	W	1600	2400	3900	5200	7600	9400
Fan	Air flow	mc/h	4060	4060	8060	8060	8060
	Max. absorbed power	W	260	260	2 x 260	2 x 260	2 x 260
Condenser		Air condenser (copper/aluminium)					
Evaporator		Brazed plates					
Electronic thermoregulator		Setting range from -25 to -10°C					
Pump (**)	Flow rate	l/min	13.3 - 70	13.3 - 70	13.3 - 70	13.3 - 70	48 - 250
	Head	bar	2.7 - 1.3	2.7 - 1.3	2.7 - 1.3	2.7 - 1.3	3.1 - 1.3
	Max. absorbed power	W	625	625	625	625	1509
Thermoplastic tank (nom. capacity (**))	l	23	23	65	65	65	65
Refrigerant gas		R 404A					
Noise level (at 1 m distance)	db (A)	70	70	70	70	70	70
Frame colour		RAL 7035					
Frame type		ECP3L-B	ECP3L-B	D3-1C	D3-1C	D3-1C	D3-1C

Technical drawings available in the **DOWNLOAD** area of our Web site

Weights & dimensions

Empty weight (approx.)	kg	100	100	320	320	320	320
Packaging weight (approx.)	kg	110	110	340	340	340	340
Dimensions (W x D x H)	mm	665 x 656 x 1180			750 x 1410 x 1380		
Packaging dimensions (W x D x H) (***)	mm	1000 x 800 x 1580			850 x 1595 x 1580		

Notes

(*) Performance data refers to outlet fluid at -15°C and ambient temperature +32°C

(**) Flow rate referred to pure water

(***) Standard packaging: cardboard box placed on pallet

Cooling capacity data is based on ASHRAE graphs supplied by the compressor manufacturers

Maximum temperature of inlet fluid: 0°C

Maximum and minimum ambient temperature: from +10 to +40°C

Minimum and maximum ambient relative humidity (without condensation): from 10 to 85% - Maximum ambient altitude: 2000 m

Minimum and maximum stocking temperature: from +5 to +45°C

Hydraulic connections: see technical drawings available in the **DOWNLOAD** area of our website - All measures on technical drawings are in millimetres unless otherwise specified

EURO COLD reserves the right to carry out modifications without prior notice

Indications for the use of pure antifreeze based on working temperature

Outlet fluid temperature °C	Glycol %
-15	35
-20	40
-25	50